



## BREMENOL SAFE TRANZ ATF III DEXRON III

### Automatic Transmission Fluid

#### GENERAL PROFILE

Safe tranz is automatic transmission fluid manufactured from high quality synthetic base fluids and a balanced additive package. It has superior performance in terms of frictional characteristics, seal compatibility, oxidation stability, low temperature fluidity and resistance to high temperatures encountered during severe operating conditions.

#### FEATURES & BENEFITS

1. It has excellent oxidation stability and frictional characteristics
2. It improves clutch durability.
3. It has low foaming tendency.
4. It has high thermal stability.
5. Excellent protection against wear.

#### SPECIFICATION

GM DEXRON IIIH, FORD MERCON, ALLISON C-4/ TES-389B

#### APPLICATION OF USE

Recommended for use in automatic transmissions, powershift transmissions, tranaxles, torque converters, hydrostatic drives, fluid couplings, fluid clutches, transfer boxes, brake boosters, leveling systems, hydraulic systems etc. It can also be used as power steering fluid. Please follow OEM advice.

#### PHYSICAL CHARACTERISTICS

#### TEST METHOD

#### TYPICAL VALUE

Appearance		Red
Density @ 25°C, g/cc	ASTM D4052	0.86
K. Viscosity @ 100°C, cSt	ASTM 7042	36.41
K. Viscosity @ 40°C, cSt	ASTM 7042	7.14
Viscosity Index	ASTM D 2270	162
Brookfield Viscosity @ -40°C, cP	ASTM D 2983	13500
Pour Point, °C	ASTM D97	-45
Flash Point, °C	ASTM D92	230

\*Typical value does not constitute a specification

#### Health and Safety

This product used as our recommendation for intended application not expected to produce any particular risk. A safety data sheet of the product is available for a simple request from your sales contact office or via internet. In case of used oil elimination, please respect the regulation and protect the environment.